

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11)Publication number: **55064823 A**

(43)Date of publication of
application: **15. 05 . 80**

(51)Int. Cl **B01D 53/04**
B01J 20/28

(21)Application number: **53138175**

(71)Applicant: **YAMANISHI SHIKATARO**

(22)Date of filing: **08 . 11 . 78**

(72)Inventor: **YAMANISHI SHIKATARO**

(54)MANUFACTURING METHOD OF
ALUMINOSILICATE-CONTAINING ELASTIC
PLATE HAVING EFFECTIVE
ABSORBABILITY OF OFFENSIVE ODOR

synthetic resin, an unvulcanized foamed rubber or synthetic resin, or a mixture of these, is mixed with an aluminosilicate, e.g., activated clay, acid clay, etc., to obtain a rubbery elastic plate or a spongy rubber elastic plate. The rubbery elastic substance can be widely used as an intermediate insertion for footwears, a deodorant for refrigerator, etc., and also can be easily manufactured.

(57)Abstract:

PURPOSE: To manufacture a rubbery elastic substance having good hygroscopicity and high offensive odor absorbability by mixing an unvulcanized rubber or unvulcanized foamed rubber with an aluminosilicate such as activated clay, etc.

COPYRIGHT: (C)1980,JPO&Japio

CONSTITUTION: An unvulcanized rubber or